URINALS

Siphonic urinal CAPRINO PLUS 84206.6



TECHNICAL DATA

Order no.	84206.6	Mounti
Certified to	EN 80, EN 13407, EN 15091	
matching for	LIS CU3 Concealed frame for urinal with	
	integrated control, order no. 89266.5	
Specification	1-I flushing electronic controlled siphonic urinal	
	Electronic control for battery (4x AA 1,5 V)	Mounti
	Only in combination with fixing set,	
	order no. 89280.8	
Water inlet	concealed, 1/2"	
Outlet	horizontal or vertical	
Flushing	11	Colours
Flushing rate	minimum 0.3 l/s	SPECI
Weight	20,0 kg	Siphon
Mounting acc. incl.	Electronic control system battery with all	electror
	mounting accessories	EN 80,
	Charge 000 – without fly, 1-litre siphon with	1-l flush
	horizontal and vertical outlet DN 40 (standard CH)	flushing
	Charge 400 – with fly, 1-litre siphon with hori-	electror
	zontal and vertical outlet DN 40 (standard CH)	1-litre s
	Charge 401 – without fly, 1-litre siphon with	Europe
	horizontal and vertical outlet DN 50 (standard	siphon
	Europe, except CH and UK)	Special
	Charge 411 – with fly, 1-litre siphon with	Further
	horizontal and vertical outlet DN 50 (standard	cealed
	Europe, except CH and UK)	Order n

Mounting acc. incl.	Charge 407 – without fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Charge 417 – with fly, 2-litre siphon with horizontal outlet DN 40 (standard UK) Wall fixing set M8 LAUFEN, order no. 89280.8
Mounting acc. excl.	Stone screw fixing set M8 Adaption set for stone screws M10, order no. a9281.6
	Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-CAPRINO PLUS, sanitary ceramic electronic control

EN 80, EN 13407, EN 15091, dimensions 320 x 350 x 645 mm 1-I flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing rate minimum 0.3 l/s electronic control system for battery with all mounting accessories, 1-litre siphon with horizontal and vertical outlet DN 50 (standard

Europe, except CH and UK) and outlet DN 40 (standard CH), 2-litre


siphon with horizontal outlet DN 40 (standard UK)


Special feature: Vacuum and performance tested


Further options: Surface refinement LCC (only white), with fly, LIS CU3 concealed frame for urinal with integrated control

Order no. 84206.6

TECHNICAL DRAWINGS / S 1 : 20







LAUFEN