

KT0005

White finish



KT0005C **Bright finish** 



**KT0005CS** Satin finish

## **General description**

- Kit for recessed Saniflow hand dryer (hand dryer not included).
- The kit for recessed Saniflow makes the Saniflow hand dryer suitable for the compliance of the ADAAG norm (US) - that limits to 4 inches (100mm) the horizontal projection of the devices installed in bathrooms for public use-, bestowing on that hand dryer the quality of "specific for the disabled".
- Maximum robustness and vandal-proof.
- Excellent integration and aesthetical level.

## **Components and materials**

- CABINET: made of electro-zinced iron, 1.5 mm thick. It includes 4 M5 bolts welded on top of the base plate for fitting the Saniflow hand dryer.
- FRAME: 1.5 mm thick, made of steel white finish (KT0005) or AISI 304 stainless steel bright finish (KT0005C) or satin finish (KT0005CS), with 4 screw holes of Ø 9 mm for mounting on the wall.
- GASKET: made of grey rubber, offers a reinforcing outside protection that minimizes vibrations and noise.
- NUTS AND BOLTS: for fitting the dryer to the kit and the frame to the wall. It includes: 4 nuts DIN 934 M5, 4 washers DIN 125 M5, 4 stainless steel screws DIN 7981 32 x 5,5 mm and 4 wall plugs F8.


NOTE: nuts and bolts for the mounting of the cabinet to the wall are not included. Use of stainless steel nuts and bolts is recommended.


## **Technical specifications**


KIT FOR RECESSED SANIFLOW

Dimensions	345 x 440 x 118 mm
Cabinet thickness	1.5 mm
Frame thickness	1.5 mm

## **Dimensions**







Dimensions: ±4%

Hand dryer not included

Mediclinics, , S.A., reserves the right to make changes and/or modifications to the products and their specifications without prior notice. Review 06-19 © mediclinics S.A.

