

NOVA TOWEL RAIL
NOVA HAVLU ASKLIĞI

2000 x 590 in brushed finish shown with Azur valves

304 GRADE STAINLESS STEEL
304 KALITE PASLANMAZ ÇELİKBRUSHED FINISH
FİRÇA YÜZEYİMAX. WORKING PRESSURE 4 BAR
MAX ÇALIŞMA BASINCI 4 BARHYDRONIC
MERKEZİ SİSTEM KULLANIMA UYGUNELECTRIC HEATING WHEN INSTALLED IN VERTICAL POSITION
DİKEY MONTAJDA ELEKTRİKLİ KULLANIMA UYGUNYEARS GUARANTEE
YIL GARANTİ

Size Ebat mm	(W) Width Genişlik mm	(H) Height Yükseklik mm	(K) Pipe Centers Aks Aralığı mm K1 - K2 -K3	Tube Quantity Boru Sayısı pcs-adet	Weight Ağırlık kg	HEAT CAPACITY / ISIL KAPASİTE	
						$\Delta t = 60^\circ \text{C}$ (85/75/20°C) kcal/h / watt / btu/h	$\Delta t = 50^\circ \text{C}$ (75/65/20°C) kcal/h / watt / btu/h
1200 x 310	310	1200	390-280-1130	8	14.4	420 / 489 / 1668	325 / 378 / 1290
1200 x 430	430	1200	510-400-1130	11	19.2	578 / 673 / 2295	447 / 520 / 1774
1200 x 510	510	1200	590-480-1130	13	22.3	685 / 796 / 2717	529 / 615 / 2099
1200 x 590	590	1200	670-560-1130	15	25.5	790 / 918 / 3133	611 / 710 / 2423
1500 x 310	310	1500	390-280-1430	8	17.4	516 / 600 / 2048	398 / 463 / 1580
1500 x 430	430	1500	510-400-1430	11	23.2	709 / 826 / 2817	547 / 637 / 2174
1500 x 510	510	1500	590-480-1430	13	27.1	839 / 976 / 3331	648 / 753 / 2570
1500 x 590	590	1500	670-560-1430	15	31	968 / 1126 / 3843	747 / 869 / 2966
2000 x 310	310	2000	390-280-1930	8	22.3	656 / 764 / 2606	510 / 594 / 2027
2000 x 430	430	2000	510-400-1930	11	29.9	902 / 1051 / 3585	702 / 817 / 2788
2000 x 510	510	2000	590-480-1930	13	34.9	1066 / 1241 / 4234	829 / 965 / 3295
2000 x 590	590	2000	670-560-1930	15	40.1	1233 / 1434 / 4894	959 / 1115 / 3805

All models (except electric ones) can be installed horizontally or vertically. A diverter is supplied with mounting brackets (please refer to instructions) in order to allow connection options as shown below.

Yeşil renkli aks aralıkları Azur vanalar için geçerlidir.
Green coloured pipe centers are only valid for Azur valves

