



2000 x 310 in brushed finish shown with Azur valves

TUANA PEGS
TUANA BORNOZ ASKILIĞINOVA TOWEL RAIL
NOVA HAVLU ASKILIĞI304 GRADE STAINLESS STEEL
304 KALITE PASLANMAZ ÇELİKBRUSHED FINISH
FİRÇA YÜZEYİMAX. WORKING PRESSURE 4 BAR
MAX. ÇALIŞMA BASINCI 4 BARHYDRONIC
MERKEZİ SİSTEM KULLANIMA UYGUNELECTRIC HEATING WHEN INSTALLED IN VERTICAL POSITION
DİKEY MONTAJDA ELEKTRİK KULLANIMA UYGUNYEARS GUARANTEE
YIL GARANTİ

Size Ebat mm	(W) Width Genişlik mm	(H) Height Yükseklik mm	(K) Pipe Centers Aks Aralığı mm K1 - K2 - K3	Tube Quantity Boru Sayısı pcs-adet	Weight Ağırlık kg	HEAT CAPACITY / ISIL KAPASİTE	
						$\Delta t = 60^\circ \text{C}$ (85/75/20° C) kcal/h / watt / btu/h	$\Delta t = 50^\circ \text{C}$ (75/65/20° C) kcal/h / watt / btu/h
1000 x 310	310	1000	390-260-930	7	9.7	321 / 373 / 1273	252 / 293 / 1000
1000 x 390	390	1000	470-340-930	9	11.8	409 / 475 / 1621	321 / 373 / 1273
1000 x 510	510	1000	590-460-930	12	15	540 / 628 / 2143	423 / 493 / 1682
1200 x 310	310	1200	390-260-1130	7	11.2	381 / 444 / 1515	298 / 347 / 1184
1200 x 390	390	1200	470-340-1130	9	13.7	484 / 563 / 1921	378 / 440 / 1501
1200 x 510	510	1200	590-460-1130	12	17.4	636 / 741 / 2528	497 / 579 / 1976
1500 x 310	310	1500	390-260-1430	7	13.4	475 / 552 / 1885	369 / 429 / 1464
1500 x 390	390	1500	470-340-1430	9	16.5	601 / 699 / 2386	466 / 543 / 1853
1500 x 510	510	1500	590-460-1430	12	21	789 / 918 / 3133	612 / 713 / 2433
2000 x 310	310	2000	390-260-1930	7	17.2	628 / 731 / 2496	492 / 573 / 1955
2000 x 390	390	2000	470-340-1930	9	21.1	794 / 924 / 3154	622 / 724 / 2470
2000 x 510	510	2000	590-460-1930	12	26.2	1215 / 1044 / 4147	818 / 952 / 3248

All models (except electric ones) can be installed horizontally or vertically. A diverter is supplied with mounting brackets (please refer to instructions) in order to allow connection options as shown below.

Yeşil renkli aks aralıkları Azur vanalar için geçerlidir.
Green coloured pipe centers are only valid for Azur valves

