

FRAME 25 MIRROR CABINET

Mirror cabinet with LED light

40830.1 / 40830.2

40831.1 / 40831.2

40832.1 / 40832.2

40835.1 / 40835.2

40836.1 / 40836.2

40837.1 / 40837.2



TECHNICAL DATA

Order no.	40830.1 / door hinge left, with sensor switch, 2 sockets (EU)	Dimensions (WxHxD)	450 x 750 x 150 mm
	40831.1 / door hinge left, hardwired for room switch, 2 sockets (CH)	Specification	Body – Inner part anodized aluminum (sidewall top, bottom), back wall grey melamine coated MDF
	40832.1 / door hinge left, hardwired for room switch		Door – Glass 3+3 mm
	40835.1 / door hinge left, bottom ambient light, with sensor switch, 2 sockets (EU)		1 door with inside and outside mirrors, including handle (optional usable)
	40836.1 / door hinge left, hardwired for room switch, bottom ambient light with sensor switch, 2 sockets (CH)		With vertical LED light
	40837.1 / door hinge left, hardwired for room switch, bottom ambient light with sensor switch, without sockets		2x 14W/m, 4000 Kelvin (daylight), IP44, 230V
	40830.2 / door hinge right, with sensor switch, 2 sockets (EU)		3 glass shelves (adjustable)
	40831.2 / door hinge right, hardwired for room switch, 2 sockets (CH)	Weight	14,0 kg
	40832.2 / door hinge right, hardwired for room switch	Accessories excl.	Accessories set consisting of 1 organizer, cosmetic mirror and magnetic bar self adhesive, order no. 49060.0
	40835.2 / door hinge right, bottom ambient light, with sensor switch, 2 sockets (EU)	Mounting acc. incl.	Installation set, order no. 49063.0
	40836.2 / door hinge right, hardwired for room switch, bottom ambient light with sensor switch, 2 sockets (CH)	Mounting acc. excl.	Installation frame set for mirror cabinet 450 mm, aluminum, dimensions 480 x 780 x 30 mm, order no. 40838.0 (only 40831.1, 40832.1, 40831.2, 40832.2 in connection with colour option 144)
	40837.2 / door hinge right, hardwired for room switch, bottom ambient light with sensor switch, without sockets	Mounting information	The fortification walls must meet the requirements of the furniture in terms of weight and the supplied fasteners. This can not be guaranteed, another method of attachment is chosen. 230V power supply required. Attention: Clearance for sensor switch min. 15 cm below mirror cabinet!
Certified to	IP44	Colours side wall	144 – Mirror, 145 – Glass with white backing (cover)

TECHNICAL DRAWINGS / S 1 : 20

