# WATERWORKS

ETOILE ETXS54

Etoile Exposed Thermostatic System with 4 1/2" Shower Rose, Handshower and White Porcelain Lever Handle



#### **TECHNICAL DETAILS**

ADA Compliance: Yes
Adjustable versus Fixed Spray: Fixed Spray
Assembly / Configuration: Completely Assembled
Diameter of Head: 4 1/2"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"
Flow Restriction Options: 2.0, 1.75, 1.5
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 59"

Depth / Width: 15"
Height: 54"
Inlet Connection Size: 3/4"
Inlet Connection Type: Female NPT
Inlet Supply Spread Maximum: 10 1/4"
Inlet Supply Spread Minimum: 10 1/4"
Installation Type: Wall Mounted
Integrated Diverter: Y

Length: 15" Number of Handles: Three Pivot: Y Primary Material: Brass

Restricted Maximum Flow Rate: 2.5 gpm

Suggested Application: Bath Valve Material: Brass

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L Shown in Etoile Exposed Thermostatic System with 4 1/2" Shower Rose and Handshower and White

## **INSPIRATION**

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

## **CODES & STANDARDS**

Code # ETSV54: Certified with IAPMO & State of MA. Complies with ASME A112.18.1/CSA B125.1, ANSI 117.1 ADA & ASTM E 1621-05.

## **PRODUCT FEATURES**

White porcelain lever and metal cross handles

Swiveling 4 1/2" shower rose. Allows bather to adjust temperature of all waterway outlets with a hot limit safety stop providing anti-scald protection. Two Shut off controls allow outlets to be controlled independently Features graceful, elongated curves

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

 $Stocked\ in\ 2.5gpm\ (9.5L/min)\ flow\ rate.\ Alternate\ flow\ regulation\ of\ 1.75gpm\ (6.6/min)\ also\ availble\ as\ special$ 

## **CERTIFICATIONS**



# PRODUCT (NOTES)

Valve Included

ETOILE ETXS54

Etoile Exposed Thermostatic System with 4 1/2" Shower Rose, Handshower and White Porcelain Lever Handle

