ETOILE

ETXS58

Etoile Exposed Thermostatic System with 8" Shower Rose, Handshower and White Porcelain Lever Handle



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Assembly / Configuration: Completely Assembled Diameter of Head: 8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 59" Depth / Width: 30" Height: 60" Inlet Connection Size: 3/4" Inlet Connection Type: Female NPT Inlet Supply Spread Maximum: 10 1/4" Inlet Supply Spread Minimum: 10 1/4" Installation Type: Wall Mounted Integrated Diverter: Y Length: 17" Number of Handles: Three Pivot: Y Primary Material: Brass Restricted Maximum Flow Rate: 2.5 gpm Suggested Application: Bath Valve Material: Brass Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN ETOILE EXPOSED THERMOSTATIC SYSTEM WITH 8" SHOWER ROSE AND HANDSHOWER AND WHITE PORCELAIN

INSPIRATION

Defined elegance. Etoile has a European sophistication with a timeless sense of chic.

CODES & STANDARDS

Code # ETSV58: Certified with IAPMO & State of MA. Complies with ASME A112.18.1/CSA B125.1, ANSI 117.1 ADA & ASTM E 1621-05.

PRODUCT FEATURES

White porcelain lever and metal cross handles

Swiveling 8" shower rose. Allows bather to adjust temperature of all waterway outlets with a hot limit safety stop providing anti-scald protection. Two Shut off controls allow outlets to be controlled independently

Features graceful, elongated curves

Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass

Stocked in 2.5gpm (9.5L/min) flow rate. Alternate flow regulation of 1.75gpm (6.6/min) also availble as special





PRODUCT (NOTES)

Valve Included

ETOILE

ETXS58

Etoile Exposed Thermostatic System with 8" Shower Rose, Handshower and White Porcelain Lever Handle

