

HENRY

HNKM70

Henry One Hole Gooseneck Kitchen Faucet with Pull-Down Spray and Metal Lever Handle



SHOWN IN HENRY ONE HOLE GOOSENECK KITCHEN FAUCET WITH PULL-DOWN SPRAY AND METAL LEVER HANDLE

TECHNICAL DETAILS

Adjustable versus Fixed Spray: Adjustable Spray
Deck Thickness Maximum: 3 1/4"
Deck Thickness Minimum: 1/4"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"
Flow Restriction Options: 2.0, 1.75, 1.5
Handle Turn Angle: Quarter Turn
Handshower / Spray Hose Length: 49"
Depth / Width: 11 3/4"
Height: 17"
Inlet Connection Size: 3/8"
Inlet Connection Type: Compression Connector Hoses
Length: 11 3/4"
Primary Material: Brass
Restricted Maximum Flow Rate: 2.2 gpm
Spout Swivel: Y
Spray Included in Unit: Y
Suggested Application: Bar, Kitchen, Laundry
Valve Material: Ceramic
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 30.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

PRODUCT FEATURES

The stately single hole fitting stands on a tall well formed pillar with a tapered lever handle. Practical as well as beautiful, this fitting has a hand spray for washing vegetables, rinsing the sink or cleaning pots.

Spray features a trigger to switch between aerated stream and jet spray.

Spray is held in place with a counter weighted magnet.

Handle rotates toward the front to prevent contact with backsplash.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also

CERTIFICATIONS



WATERWORKS

HENRY

HNKM70

Henry One Hole Gooseneck Kitchen Faucet with Pull-Down Spray and Metal Lever Handle

