

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

RESIDUAL CURRENT OPERATED CIRCUIT-BREAKER (WITH
TYPE F AND B) WITHOUT INTEGRAL OVERCURRENT
PROTECTION FOR HOUSEHOLD AND SIMILAR USES

Name and address of the applicant

SCHNEIDER ELECTRIC INDUSTRIES SAS
31, RUE PIERRE MENDES - EYBENS
38050 GRENOBLE CEDEX 9 (FRANCE)

Name and address of the manufacturer

SCHNEIDER ELECTRIC ESPAÑA, S.A.
Camino BARRANQUET, 57
46133 MELIANA (Valencia/València - Spain)

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

See references on the Annex

Trademark (if any)

SCHNEIDER ELECTRIC

Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

Commercial name "RCCB Multi 9 Monoconnect"
See references on the AnnexAdditional information (if necessary may also be
reported on page 2) Additional Information on page 2A sample of the product was tested and found
to be in conformity withIEC 61008-2-1:1990
IEC 61008-1:2010
IEC 61008-1:2010/AMD1:2012
IEC 61008-1:2010/AMD2:2013
IEC 62423:2009As shown in the Test Report Ref. No. which forms part
of this CertificateGS314/20, GS315/20, GS316/20, GS317/20, GS318/20, GS319/20,
GS320/20, GS321/20, GS322/20, GS333/20, GS334/20, GS83/15,
GS84/15, GS85/15, GS86/15, GS87/15, GS88/15, GS89/15, GS90/15,
GS91/15, GS92/15, GS93/15, GS94/15, GS95/15, GS96/15, GS97/15,
GS98/15, GS99/15, GS100/15, GS101/15, GS102/15, GS103/15,
GS104/15, GS105/15, GS127/15

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2020-12-23

Signature: Rafael GARCÍA MEIRO
Chief Executive Officer



Ref. Certif. No.

ES2360-A1-AENOR

Other factories:

SCHNEIDER ELECTRIC INDIA PRIVATE LIMITED
No. 172, POONAMALLEE BY PASS ROAD, POONAMALLEE
600056 CHENNAI (Tamil Nadu - India)

Additional information (if necessary)

Date: 2020-12-23

Signature:

Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2360-A1-AENOR

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

Trade Mark: SCHNEIDER ELECTRIC

Product: RESIDUAL CURRENT OPERATED CIRCUIT-BREAKER (WITH TYPE F AND B) WITHOUT INTEGRAL OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR USES

Type Ref.	Type	N° of poles	Rated current (In)	Rated voltage (Un)	Rated residual current (I _{dn})	Frequency	Rated residual making and breaking capacity (I _{dm})	Rated making and breaking capacity (I _m)	Rated conditional short-circuit current (I _{nc})	Rated conditional residual short.circuit current (I _{dc})	Additional information
IDSM2P2530A	A	2P	25A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P2530AC	AC	2P	25A	230/240V~	30mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM2P2530ASI	ASI	2P	25A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P2530F	F	2P	25A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P2530FSI	F-SI	2P	25A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P25300AC	AC	2P	25A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM2P25300SA	A-S	2P	25A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P25300SAC	AC-S	2P	25A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P25300SASI	ASI-S	2P	25A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P4030A	A	2P	40A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P4030AC	AC	2P	40A	230/240V~	30mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM2P4030ASI	ASI	2P	40A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P4030F	F	2P	40A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P4030FSI	F-SI	2P	40A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P40300AC	AC	2P	40A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM2P40300SA	A-S	2P	40A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P40300SAC	AC-S	2P	40A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P40300SASI	ASI-S	2P	40A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM2P6330A	A	2P	63A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM2P6330AC	AC	2P	63A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM2P6330ASI	ASI	2P	63A	230/240V~	30mA	50 Hz	2500A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM2P63300AC	AC	2P	63A	230/240V~	300mA	50 Hz	800A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM2P63300SA	A-S	2P	63A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM2P63300SAC	AC-S	2P	63A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM2P63300SASI	ASI-S	2P	63A	230/240V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM2P8030AC	AC	2P	80A	230/240V~	30mA	50 Hz	800A	800A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM2P80300AC	AC	2P	80A	230/240V~	300mA	50 Hz	800A	800A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P25100AC	AC	4P	25A	400/415V~	100mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)

Type Ref.	Type	Nº of poles	Rated current (In)	Rated voltage (Un)	Rated residual current (I _{dn})	Frequency	Rated residual making and breaking capacity (I _{dm})	Rated making and breaking capacity (I _m)	Rated conditional short-circuit current (I _{nc})	Rated conditional residual short.circuit current (I _{dc})	Additional information
IDSM4P2530A	A	4P	25A	400/415V~	30mA	50 Hz	1500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM4P2530AC	AC	4P	25A	400/415V~	30mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM4P2530ASI	ASI	4P	25A	400/415V~	30mA	50 Hz	1500A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM4P25300AC	AC	4P	25A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (3) (5) (6) (7)
IDSM4P25300SA	A-S	4P	25A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM4P25300SAC	AC-S	4P	25A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM4P25300SASI	ASI-S	4P	25A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(1) (4) (5) (6) (7)
IDSM4P40100AC	AC	4P	40A	400/415V~	100mA	50 Hz	630A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P4030A	A	4P	40A	400/415V~	30mA	50 Hz	1500A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P4030AC	AC	4P	40A	400/415V~	30mA	50 Hz	630A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P4030ASI	ASI	4P	40A	400/415V~	30mA	50 Hz	1500A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P40300AC	AC	4P	40A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P40300SA	A-S	4P	40A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P40300SAC	AC-S	4P	40A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P40300SASI	ASI-S	4P	40A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P63100AC	AC	4P	63A	400/415V~	100mA	50 Hz	630A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P6330A	A	4P	63A	400/415V~	30mA	50 Hz	800A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P6330AC	AC	4P	63A	400/415V~	30mA	50 Hz	800A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P6330ASI	ASI	4P	63A	400/415V~	30mA	50 Hz	800A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P63300AC	AC	4P	63A	400/415V~	300mA	50 Hz	800A	630A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P63300SA	A-S	4P	63A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P63300SAC	AC-S	4P	63A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P63300SASI	ASI-S	4P	63A	400/415V~	300mA	50 Hz	630A	630A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P8030A	A	4P	80A	400/415V~	30mA	50 Hz	800A	800A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P8030AC	AC	4P	80A	400/415V~	30mA	50 Hz	800A	800A	10000A	10000A	(2) (3) (5) (6) (7)
IDSM4P8030ASI	ASI	4P	80A	400/415V~	30mA	50 Hz	800A	800A	10000A	10000A	(2) (4) (5) (6) (7)
IDSM4P80300AC	AC	4P	80A	400/415V~	300mA	50 Hz	800A	800A	10000A	10000A	(2) (3) (5) (6) (7)

- (1) Output terminal in Copper with tin coating Sn5 or alternate in Steel with tin coating Sn5
- (2) Output terminal in Copper with tin coating Sn5
- (3) -5/40°C
- (4) -25/40°C
- (5) Variants of Base/Cover in Grey or White
- (6) Variants of Toggle in Black, Grey, Orange or White
- (7) Variants of Test Button in Black or White