KOHLER_®

Underscore® Rectangle

5' VibrAcoustic® Bath K-1167-VB

Features

- VibrAcoustic calms and soothes with sound vibration technology.
- Six concealed speakers send sound waves through the water to gently massage the body.
- Four original instrumental compositions offer different levels of relaxation.
- Syncs with devices enabled with BLUETOOTH[®] wireless technology including smartphones, MP3 players, tablets, and laptops located up to 33 feet away.*
- Customize your experience with the high-resolution color touch screen.
- Fully-adjustable volume above and below the water.
- Functions as a hydrotherapy bath when full of water and a stereo system when empty.
- Clearflo slotted overflow for deep soaking.
- Includes 25 feet of wiring and amplifier.

Material

Acrylic.

Hydrotherapy

VibrAcoustic.

Installation

- Requires 110V electrical service.
- Drop-in.

Required Products/Accessories

K-7271 Brass Slotted Overflow Bath Drain K-7272 PVC Slotted Overflow Bath Drain

Recommended Products/Accessories

1184460 Undermount installation kit K-1491 Bath/Whirlpool Pillow K-1601 Bath/Whirlpool Footstop K-531 Under-Mount Installation Kit K-706000-D3 Frameless Sliding Bath Door K-706003-L Frameless Sliding Bath Door K-706004-D3 Frameless Sliding Bath Door K-706004-L Frameless Sliding Bath Door K-706007-L Frameless Sliding Bath Door K-706007-L Frameless Sliding Bath Door K-1177 Vinyl Tiling-in Bead K-23726 Drain treatment K-23732 Tub & shower cleaner



ADA

Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2 ADA ICC/ANSI A117.1

KOHLER[®] Plastic Baths and Receptors Lifetime Limited Warranty

See website for detailed warranty information.

The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	lce™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey

7 Black Black™






Underscore® Rectangle

5' VibrAcoustic® Bath

K-1167-VB



Required Electrical Service

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD). Amplifier: 120 V, 15 A, 50/60 Hz

Technical Information

All product dimensions are nominal.

•	
Installation:	Drop-in
Drain location:	End
Basin area, bottom:	42-3/8" x 20" (1076 mm x 508 mm)
Basin area, top:	54-3/8" x 24-5/16" (1381 mm x 618 mm)
Weight:	75 lbs (34 kg)
Minimum floor load:	50 lbs/ft² (244.1 kg/m²)
Water depth:	15-1/16" (383 mm)
Water capacity:	59.8 gal (226.4 L)
Cutout:	Drop-in, 59-1/2" x 28-1/2" (1511 mm x
	724 mm)
Electrical component rating:	Amplifier: 120 V, 1.1 A, 50/60 Hz
Amplifier channels:	2 at 15 W per channel
	2 at 30 W per channel

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Kit is required for under-mount installations (sold separately).

Control amplifier fits 16" (406 mm) center studs. 25' (7.6 m) cables are included.

ADA compliant when installed to the specific requirements of these regulations.

