

Choreograph® 36"x36"x96" Wall Kit **K-97611-T01**

Features

- Includes three 36" x 96" walls and two 96" corner joints.
- No need to install trim. Factory-installed edge provides a finished look for walls.
- Joint system hides caulk and silicone, leaving fewer places for mold to grow and simplifying cleaning.
- Coordinates with Choreograph shower accessories and storage (sold separately).

Material

- Serica®, KOHLER's proprietary composite material, offers unparalleled durability, strength, and aesthetic beauty.
- Matte finish complements any decor.
- Choreograph walls made from Serica are repairable. KOHLERs ASR network can assist in repairing surface defects, cracks, etc. Customer service can assist in scheduling a repair. Repair kit part numbers: Patterned panels: 1374534-NY, 1374534-G9, 1374534-96. Solid Panels: 1283194 - *.

Installation

- In-field trimmable.
- Adheres to water-resistant wallboard.
- For a 36" x 36" x 96" three-wall alcove or smaller.

Recommended Products/Accessories

K-23732 Tub & shower cleaner

Included Components

Product consists of:

K-97601-T01 36"x96" Wall Panel K-97601-T01 36"x96" Wall Panel K-97601-T01 36"x96" Wall Panel

K-97635 96" Corner Joint



Codes/Standards

ASTM E162 ASTM E662

KOHLER® Limited Warranty – Choreograph™ Walls and Accessories

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Descriptio
	0	White
	96	Biscuit
	NY	Dune
	G9	Sandbar







Choreograph®

36"x36"x96" Wall Kit **K-97611-T01**







Technical Information

All product dimensions are nominal.

Installation: Three-wall alcove
Material Thickness: 3/16" (5 mm)

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

Corner joints (optional) allow for 3/8" (10 mm) adjustment for out-of-plumb conditions or uneven cuts.

If installing accessories, install 2x4 backing for handrails, shelves, and shower hooks and 2x10 backing for the flip down seat.

Use non-solvent based construction adhesive. For installation over tile, use 100% silicone sealant.

