KUMIN - Single-lever basin mixer -Standard model - with C3 cartridge

E99981



Collection: KUMIN

Finish*:



CP - Chrome

Main features:







Features

• WEIGHT: 1.4 kg

• INSTALLATION TYPE: 1 hole

• TYPE: Single-lever

• HEIGHT UNDER SPOUT: 132

• CONNECTION: With supply hoses

• MECHANISM GUARANTEE: 5 years

• Height under aerator: 63 mm

MΔTFRIΔI · 5Δ

NORMS AND REGULATION: NF ECAU : E0 C3 A2 U3 - (Ge5) - ACS (Attestation Conformité Sonifaire) + 10 ACC LY 112

Jacob Delafon

Conformité Sanitaire) : 10 ACC LY 113

• FLOW RATE: 11 I/mn
• SPOUT PROJECTION: 100

• INSTALLATION TYPE: 1 hole

Waste

C3 water- and energy-saving cartridge - cold water delivery at onset with lever in centre position and sensitive flow control (RT2012)

Consumer benefits

• Built-in anti-scale aerator: Easy replacement with no special tool (you can use a coin) and easier cleaning


• Water flows through the faucet body with no contact with chrome or nickel: Hygiene, safety and savings


Installation benefits

• SIDE LIFT ROD: Easy to install on small washbasins, better accessibility for user

• EASIER INSTALLATION: Pre-assembled hoses

Technical drawing





Product Specification: Single-lever basin mixer - Standard model - with C3 cartridge. E99981. Collection: KUMIN. WEIGHT: 1.4 kg. MATERIAL: 54. INSTALLATION TYPE: 1 hole. NORMS AND REGULATION: NF ECAU: E0 C3 A2 U3 - (Ge5) - ACS (Attestation Conformité Sanitaire): 10 ACC LY 113. TYPE: Single-lever. FLOW RATE: 11 l/mn. HEIGHT UNDER SPOUT: 132. SPOUT PROJECTION: 100. CONNECTION: With supply hoses. INSTALLATION TYPE: 1 hole. MECHANISM GUARANTEE: 5 years. Waste. Height under aerator: 63 mm. C3 water- and energy-saving cartridge - cold water delivery at onset with lever in centre position and sensitive flow control (RT2012).