

REGULATOR

RG3T10

Regulator Three Way Thermostatic Diverter Valve Trim with Black Lever Handle



SHOWN IN REGULATOR THREE WAY THERMOSTATIC DIVERTER VALVE TRIM WITH BLACK LEVER HANDLE | RG3T10

TECHNICAL DETAILS

Control Valve Rough-in Depth Maximum: 4 3/4"
Control Valve Rough-in Depth Minimum: 3 1/8"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 2 1/2"
Depth / Width: 3 1/2"
Height: 6 1/2"
Length: 3 3/4"
Primary Material: Brass
Suggested Application: Bath
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

PRODUCT FEATURES

Matte Black Lever Handle

For use with a Thermostatic shower system and three waterway outlets such as a handshower, shower head, or tub spout

Stocked in Nickel, Chrome and Unlacquered Brass


Requires valve rough GUDV66(USA) or GU66DV(UK) sold separately.



REGULATOR

RG3T10


Regulator Three Way Thermostatic Diverter Valve Trim with Black Lever Handle




TOP VIEW SCALE: 3"=1'-0"



ISO VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"