WATERWORKS

REGULATOR RGKM51

Regulator Gooseneck Double Spout Marquee Kitchen Faucet with Metal Wheel Handles and Spray



TECHNICAL DETAILS

Deck Thickness Maximum: 2" Deck Thickness Minimum: 1/4" Handle Spread Maximum: 12" Handle Spread Minimum: 6"

Handle Turn Angle: Quarter Turn Each Way Handshower / Spray Hose Length: 79"

Depth / Width: 12 3/8" Height: 15 7/8"

Inlet Connection Size: 3/8"

Inlet Connection Type: Compression Connection Hoses

Integrated Diverter: Y Integrated Spray: N Length: 30 3/8" Primary Material: Brass

Restricted Maximum Flow Rate: 2.2 gpm

Spout Swivel: Y Spray Included in Unit: Y

Suggested Application: Bar, Kitchen, Laundry

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 30.0 psi Water Pressure Recommended: 45.0 psi

l Shown in regulator gooseneck double spout marquee kitchen faucet with metal wheel handles and

INSPIRATION

A play on industrial controls from the early 1900s, when pride was lavished on parts. Translated to handcrafted, fittings project rugged beauty through powerful, detailed shapes.

CODES & STANDARDS

Code # RGKM50: CEC

PRODUCT FEATURES

Casted brass temperature mixing valve. The user rotates the center control handle for preferred temperature. Solid brass wheel handles finished in matte black to control on/off/volume.

Built-in automatic diverters for spray operation.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in high efficiency flow options. Contact a sales associate for details.

PRODUCT (NOTES)

Drilling size requirements are 2 1/4" for mixing/spray body and 1 3/4" for faucet body.

REGULATOR RGKM51

Regulator Gooseneck Double Spout Marquee Kitchen Faucet with Metal Wheel Handles and Spray

