

SET LAUFEN PRO

Shower tray MARBOND



square
 21295.8
 21395.3



TECHNICAL DATA

Order no.	21295.8 / 1400 mm 21395.3 / 1500 mm	Mounting acc. excl.	Installation frame, adjustable height between 85-160 mm, order no. 29844.2
Certified to	EN 14257, EN 251		Antinoise set for the frame installation to fulfil DIN 4109 and SIA 181, order no. 29898.9
Dimensions	see table below		3-D sealing tape:
Depth	see table below		Sealing set 3,0 m, for sealed sides \leq 3 m, includes 1 sealing tape (width 120 mm, length 3 m), 3-D inside corner for sealing (1 piece) and 2x 3 m antinoise tape (width 30 mm), order no. 29564.2
Specification	Square shower tray made of Marbond (Gel Coat surface matt, with structure) with Antislip, Class C (DIN 51097) Removable siphon cover, stainless steel For floor-even installation or on floor installation		Additional sealing set 2,0 m, for sealed sides \geq 3 m, order no. 29564.7
Weight	21295.8 – 74,0 kg / 21395.3 – 98,0 kg		3-D sealing corners:
Mounting acc. excl.	Mounting box type DN 50, height 100 mm incl. waste, \varnothing 90 mm without cover (pre-assembled) left, order no. 29004.3, right, order no. 29004.4 Mounting box type DN 40, height 75 mm incl. waste, \varnothing 90 mm without cover (pre-assembled) left, order no. 29003.3, right, order no. 29003.4 Waste DN 50, \varnothing 90 mm without cover, order no. 29512.7 Mounting box type DN 50, height 100 mm, left, order no. 29004.1, right, order no. 29004.2 Mounting box type DN 40, height 75 mm, left, order no. 29003.1, right, order no. 29003.2		Inside corner, 1 piece, order no. 29564.3 Outside corner for floor-even installation, set 3 parts, order no. 29564.4 Dispersion sealing composition, tube 500 ml, order no. 29564.5 Noise control band, order no. 29555.1
		Otherwise	For customised Marbond shower trays order no. 21295.0 please use the order form.
		Colours	000 – White matt structured, 077 – Light grey matt structured, 078 – Anthracite matt structured, 079 – Concrete matt structured, 080 – Black matt structured

TECHNICAL DRAWINGS / S 1 : 20



Order no.	A / mm	B / mm	C / mm	D / mm
21295.8	1400	1400	700	40
21395.3	1500	1500	750	40