TECHNICAL SPECIFICATION (Auxiliary)

Column OPTIMUS - 300x1400

Information

Suspended column of 1 door with glass shelves indoor and PUSH opening system.

Materials

• Front and side panels (thickness=16mm):

- Matt white, matt black: laminated particle board lacquered with UV super matt polyester paint.

- Nordick: laminated particle board.

• Internal structure panels (thickness=16mm): laminated particle board.

• Inner shelves: 4 units: glass shelves height-adjustable (5mm of thickness)

*All boards used in the manufacture of this unit are classed as E05 with low level of formaldehyde content.

*Trim varies according to design: PVC, ABS. (edged with PUR glue)

Herrajes

• <u>Door</u>: 1 door with PUSH opening system, by an integrated ejector in the inner shelf.

• <u>Hangers:</u> Hanger with high resistance with three independent regulation, which are accesibles from the front. Certificated under DIN 68840 (equivalent to 130Kg. end loading capacity per piece). The column is reversible, only turning it aroung. (It has 2+2 hangers for right and left hand.)

Packaging dimensions and weight (mm)

	300x1400
Length mm.	330
Depth mm.	270
Height mm.	1430
Net weight Kg.	18,5
Gross weight Kg.	20,1



REVERSIBLI





Furniture finishes





Interior finishes



Furniture dimensions (mm.)



