

UNIVERSAL

GUPB87

Universal Pressure Balance Valve with Integrated Diverter for Tub/Shower Combination



SHOWN IN UNIVERSAL PRESSURE BALANCE WITH DIVERTER VALVE| GUPB87

TECHNICAL DETAILS

ADA Compliance: Yes
 Control Valve Rough-in Depth Maximum: 2 7/8"
 Control Valve Rough-in Depth Minimum: 1 7/8"
 Fittings Hole Diameter: 3 1/2"
 Depth / Width: 5 3/4"
 Height: 3 3/4"
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Copper Sweat
 Integrated Diverter: N
 Length: 4 3/4"
 Outlet Connection Size: 1/2"
 Outlet Connection Type: Sweat Shower/ NPT Tub
 Primary Material: Brass
 Safety Warnings: The risk of scalding exists until the installer has properly set the temperature high limit stop screw.
 Suggested Application: Bath
 Valve Material: Stainless Steel/ Rubber
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

CODES & STANDARDS

Code # GUSV87: ASME A112.18.1 / CSA B125.1, IAPMO, CSA, State of MA, NSF

PRODUCT FEATURES

Built in Anti-scald protection.
 For use with Waterworks Pressure Balance with Integral Diverter trims
 Do not use the bottom (tub) outlet of this product for any fittings with restricted flow, such as a handshower or body spray. The back pressure created would cause water to flow out through the top (shower) outlet. The integrated diverter on the GUPB87 would also malfunction.
 4.2 gpm unrestricted maximum flow at 45 psi

CERTIFICATIONS




PRODUCT (NOTES)

The risk of scalding exists until the installer has properly set the temperature high limit stop screw.


UNIVERSAL

GUPB87


Universal Pressure Balance Valve with Integrated Diverter for Tub/Shower Combination



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"