

UNIVERSAL

Universal 3/4" Thermostatic Valve

GUTH37



SHOWN IN UNIVERSAL 3/4" THERMOSTATIC VALVE| GUTH37

TECHNICAL DETAILS

Fittings Hole Diameter: 5 1/4"
 Depth / Width: 3 1/2"
 Height: 5 1/4"
 Inlet Connection Size: 3/4"
 Inlet Connection Type: Female NPT
 Length: 6 1/2"
 Outlet Connection Size: 3/4"
 Outlet Connection Type: Female NPT
 Primary Material: Brass
 Suggested Application: Bath
 Valve Material: Bi-metal strip
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

CODES & STANDARDS

Code # GUSV37: ASME A112.18.1 / CSA B125.1, CSA, State of Ma

PRODUCT FEATURES


- Built in Anti-scald protection.
- For use with Waterworks Thermostatic system trims, every thermostatic valve is factory tested and ready to calibrate when delivered
- 15.7 gpm unrestricted maximum flow at 45 psi
- Integrated check valves guarantee there is no crossover of hot or cold water.




UNIVERSAL

Universal 3/4" Thermostatic Valve


GUTH37



TOP VIEW SCALE: 3"=1'-0"



FRONT VIEW SCALE: 3"=1'-0"



SIDE VIEW SCALE: 3"=1'-0"