

Expanse® 5' Bath K-1118-RAW

Features

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck.
- Three heat settings allow you to customize the surface temperature.
- Curved basin and integral apron create a graceful and spacious bathing experience.
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Textured bottom surface.

Material

Acrylic.

Installation

- Right drain.
- Alcove.

Recommended Products/Accessories

K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-7259 Clearflo Bath Drain K-24916 Wireless Music Kit K-23726 Drain treatment K-23732 Tub & shower cleaner



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty See website for detailed warranty information.

Available Colors/Finishes


Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond





Expanse® 5' Bath K-1118-RAW



Required Electrical Service

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Heated Surface: 120 V, 15 A

Technical Information

All product dimensions are nominal.

Installation: Three-wall alcove

Drain location: Right

Basin area, bottom: 45-5/16" x 25-9/16" (1151 mm x 649 mm) Basin area, top: 52-9/16" x 28-1/16" (1335 mm x 713 mm)

Weight: 70 lbs (31.8 kg)

Minimum floor load: 45 lbs/ft² (219.7 kg/m²)

Water depth: 12-11/16" (322 mm)

Water capacity: 55.6 gal (210.5 L)

Electrical component Heated Surface: 120 V, 0.5 A, 60 Hz, 65

rating: W

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

