

**Floorstanding cistern Universal for floorstanding WC pan  
82866.1**



**TECHNICAL DATA**

Order no.	82866.1
Certified to	EN 14055
matching for	Floorstanding WC pan, order no. 82295.2
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 731 – 6/3-l (4,5/3-l-flush)
Water inlet	concealed top left rear 1/2"
Weight	21,5 kg
Mounting acc. incl.	Fixation set Charge 731 – corner valve for rear water inlet (3/8"-1/2") and water inlet hose

Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 290 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding cistern Universal LAUFEN PRO, sanitary ceramic EN 14055, dimensions 400/410 x 140 x 980 mm Dual-Flush 6/3-l (4,5/3-l-flush), concealed water inlet top left rear (1/2") matching floorstanding WC pan order no. 82295.2  
Special feature: water condensation insulation  
Further options: Surface refinement LCC (only white)  
Order no. 82866.1

**TECHNICAL DRAWINGS / S 1 : 20**

