

**Floorstanding cistern, two-part Universal for floorstanding WC pan
82966.0**



TECHNICAL DATA

Order no.	82966.0
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82333.7
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 882 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	21,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN- connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN- connection, order no. 89902.5 Angle valve for water inlet Water inlet hose

Colours see colour table

SPECIFICATION TEXT

Floorstanding cistern, two-part Universal Laufen-KARTELL BY LAUFEN,
sanitary ceramic
EN 14055
dimensions 400/410 x 140 x 980 mm
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
water inlet side left, side right, 3/8" brass
matching floorstanding WC pan rimless, order no. 82333.7
Special feature: water condensation insulation
Order no. 82966.0

TECHNICAL DRAWINGS / S 1 : 20

