

ASHTRAYS: SPEED WALL



| Categories: [ASHTRAYS](#), [URBAN DESIGN](#)

PRODUCT DESCRIPTION

The SPEED WALL ashtray is made on the outside of a steel sheet of 20/10 thickness, bent on the upper part to shape the sides and the cover, and of 2 steel sheets of 15/10 thickness to shape the front and the back of the ashtray. Inside there is a box in galvanized steel sheet of 10/10 thickness hooking on the triangular key lock on the front. Its removal takes place by rotating the lock and pulling out the box from underneath. On the back of the ashtray there are 2 loops for the fixing to the wall through Fischer bolts with countersunk head screws and rod with diam. going from 4,5 to 6 mm (neither is provide).

For the realization of this product made in Italy, Steel EN10111DD11 is used and later treated with a cycle of sandblasting, cataphoresis and powder coating. Such cycle is meant to guarantee the protection of the painted products, in an environment of C4 corrosion class, as requested by the UNI regulations EN ISO 12944-2. The products are eventually polyester-powder coated with RAL colours at choice.

The galvanized steel used is steel EN10346DX51D+Z and, unless otherwise stated, is not painted.

Max Dimensions:

Height: **210 mm**
Length: **150 mm**
Width: **150 mm**
Capacity: **1,4 lt**
Weight: **3 kg**

Material: [steel](#)

