

**Floorstanding cistern Universal for floorstanding WC pan  
82866.1**



**TECHNICAL DATA**

Order no.	82866.1
Certified to	EN 14055
matching for	Floorstanding WC pan, order no. 82333.1 Floorstanding WC pan rimless, order no. 82333.6
Specification	floorstanding Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,5 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose

Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding cistern Universal KARTELL BY LAUFEN, sanitary ceramic EN 14055  
 dimensions 400/410 x 140 x 980 mm  
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)  
 concealed water inlet top left rear, 1/2" brass  
 matching floorstanding WC pan, order no. 82333.1 and floorstanding WC pan rimless, order no. 82333.6  
 Special feature: water condensation insulation  
 Order no. 82866.1

**TECHNICAL DRAWINGS / S 1 : 20**

