

**Floorstanding cistern, two-part Universal for floorstanding WC pan
 82966.1**



TECHNICAL DATA

Order no.	82966.1
Certified to	EN 14055
matching for	Floorstanding WC pan, order no. 82295.2 Floorstanding WC pan rimless, order no. 82295.6
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,0 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose

Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 290 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

SPECIFICATION TEXT

Floorstanding cistern, two-part Universal LAUFEN PRO, sanitary ceramic
 EN 14055
 dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 concealed water inlet top left rear, 1/2" brass
 matching floorstanding WC pan, order no. 82295.2 and floorstanding WC pan rimless, order no. 82295.6
 Special feature: water condensation insulation
 Order no. 82966.1

TECHNICAL DRAWINGS / S 1 : 20

