

**Floorstanding cistern, two-part Universal for floorstanding WC pan
 82966.1**



TECHNICAL DATA

| | |
|---------------------|---|
| Order no. | 82966.1 |
| Certified to | EN 14055 |
| matching for | Floorstanding WC pan, order no. 82370.1 |
| Specification | Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush) |
| Water inlet | concealed top left rear, 1/2" brass |
| Weight | 21,0 kg |
| Mounting acc. incl. | Fastening kit Angle valve for rear water inlet Water inlet hose |

| | |
|---------------------|--|
| Mounting acc. excl. | for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 305 mm only LAUFEN-connection, order no. 89902.5 |
| Colours | see colour table |

SPECIFICATION TEXT

Floorstanding cistern, two-part Universal Laufen-PALACE, sanitary ceramic
 EN 14055
 dimensions 400/410 x 140 x 980 mm
 Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
 concealed water inlet top left rear, 1/2" brass
 matching floorstanding WC pan, order no. 82370.1
 Special feature: water condensation insulation
 Order no. 82966.1

TECHNICAL DRAWINGS / S 1 : 20

