

**Floorstanding cistern, two-part Universal for floorstanding WC pan  
82966.3**



**TECHNICAL DATA**

Order no.	82966.3
Certified to	EN 14055
matching for	Floorstanding WC pan rimless, order no. 82385.1
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 883 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	bottom left, 1/2" plastic
Weight	21,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 290 mm only LAUFEN-connection, order no. 89902.5 Angle valve for water inlet Water inlet hose
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding cistern, two-part Universal Laufen-THE NEW CLASSIC, sanitary ceramic  
EN 14055  
dimensions 400/410 x 140 x 980 mm  
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)  
water inlet bottom left, 1/2" plastic  
matching floorstanding WC pan rimless, order no. 82385.1  
Special feature: water condensation insulation  
Order no. 82966.3

**TECHNICAL DRAWINGS / S 1 : 20**

