

# URINALS

## Siphonic urinal TAMARO-S90 84010.3



### TECHNICAL DATA

Order no.	84010.3
Certified to	EN 80, EN 13407, EN 15091
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	IR Electronic control for 230 V
Water inlet	concealed, 1/2"
Outlet	horizontal or vertical
Flushing quantity	minimum 0.7 l - 3.0 l
Flushing capacity	minimum 0.3 l/s
Weight	20,0 kg
Mounting acc. incl.	brass inlet R 1/2", IR electronic with plug and power supply
Mounting acc. excl.	Siphon with horizontal outlet, order no. 89497.4 Siphon with vertical outlet and connection bend, order no. 89903.8 Stone screws, order no. 89406.0
Colours	see colour table

### SPECIFICATION TEXT

Siphonic urinal Laufen-TAMARO-S90, sanitary ceramic, with control system for net EN 80, EN 13407, EN 15091, dimensions 395 x 360 x 770 mm minimum 0.7 l - 3.0 l flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing rate minimum 0.3 l/s IR electronic control 230 V with plug and power supply brass inlet R 1/2"  
Special feature: Vacuum and performance tested  
Further options / accessories: siphon with horizontal outlet, siphon with vertical outlet and connection bend, LIS CU3 concealed frame for urinal with integrated control  
Order no. 84010.3

### TECHNICAL DRAWINGS / S 1 : 20

