

URINALS

Siphonic urinal TAMARO-S90

84010.4



TECHNICAL DATA

Order no.	84010.4
Certified to	EN 80, EN 13407, EN 15091
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	IR Electronic control for battery
Water inlet	concealed, 1/2"
Outlet	horizontal or vertical
Flushing quantity	minimum 0.7 l - 3.0 l
Flushing capacity	minimum 0.3 l/s
Weight	20,0 kg
Mounting acc. incl.	brass inlet R 1/2", IR electronic with 6V lithium CR-P22 battery
Mounting acc. excl.	Siphon with horizontal outlet, order no. 89497.4 Siphon with vertical outlet and connection bend, order no. 89903.8 Stone screws, order no. 89406.0
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-TAMARO-S90, sanitary ceramic, with control system for battery
EN 80, EN 13407, EN 15091, dimensions 395 x 360 x 770 mm
minimum 0.7 l - 3.0 l flush, water inlet concealed 1/2", outlet horizontal or vertical, flushing rate minimum 0.3 l/s
IR electronic control for battery, brass inlet R 1/2"
Special feature: Vacuum and performance tested
Further options / accessories: siphon with horizontal outlet, siphon with vertical outlet and connection bend, LIS CU3 concealed frame for urinal with integrated control
Order no. 84010.4

TECHNICAL DRAWINGS / S 1 : 20

