

**Siphonic urinal rimless  
CAPRINO PLUS  
84106.5**



**TECHNICAL DATA**

Order no.	84106.5	Mounting acc. excl.	1-litre siphon with horizontal and vertical outlet (rotatable) DN 40, order no. 89582.5
	Charge 000 (DN 40) / Charge 401 (DN 50)		1-litre siphon with horizontal and vertical outlet (rotatable) DN 50, order no. 89582.6
Certified to	EN 80, EN 13407, EN 15091		Stone screw fixing set M8
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5		Adaption set for stone screws M10, order no. 89281.6
Specification	Rimless 1-l flushing siphonic urinal Electronic control with Bluetooth for 230 V / 6 V Only in combination with fixing set, order no. 89280.8 Charge 000 – DN 40 Charge 401 – DN 50		Adaption set for stone screws M12, order no. 89281.4
Water inlet	concealed, Ø 35 mm, 2-6 bar	Colours	see colour table
Outlet	horizontal or vertical	<b>SPECIFICATION TEXT</b>	
Flushing	minimum 0.5 l - 3.0 l	Siphonic urinal rimless Laufen-CAPRINO PLUS, sanitary ceramic electronic controlled with Bluetooth	
Flushing rate	minimum 0.3 l/s	EN 80, EN 13407, EN 15091, dimensions 320 x 350 x 645 mm	
Weight	17,0 kg	minimum 0.5 l - 3.0 l flush, water inlet concealed Ø 35 mm 2-6 bar, outlet horizontal, flushing rate minimum 0.3 l/s	
Mounting acc. incl.	Electronic control 230 V / 6 V Wall fixing set M8 LAUFEN, order no. 89280.8 Charge 000 – 1-litre siphon with horizontal outlet DN 40 Charge 401 – 1-litre siphon with horizontal outlet DN 50	electronic control 230 V / 6 V Special feature: Vacuum and performance tested Further options / accessories: Surface refinement LCC (only white), 1-liter siphon with horizontal and vertical outlet (rotatable), LIS CU3 concealed frame for urinal with integrated control Order no. 84106.5	

**TECHNICAL DRAWINGS / S 1 : 20**

