

URINALS

Siphonic urinal TAMARO-VS 84112.5



TECHNICAL DATA

Order no.	84112.5
Certified to	EN 80, EN 13407, EN 15091
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	1-l flushing siphonic urinal Electronic control with Bluetooth for 230 V / 6 V Only in combination with fixing set, order no. 89280.8 Charge 000 – DN 40 Charge 401 – DN 50
Water inlet	concealed, 1/2"
Outlet	horizontal
Flushing	minimum 1 l - 3.0 l
Flushing rate	minimum 0.3 l/s
Weight	28,0 kg
Mounting acc. incl.	Electronic control 230 V / 6 V Wall fixing set M8 LAUFEN, order no. 89280.8 Charge 000 – 1-liter siphon DN 40 with waste connection pipe Charge 401 – 1-liter siphon DN 50 with waste connection pipe

Mounting acc. excl.	1-liter spare part siphon with horizontal outlet DN 40, order no. 89582.8 1-liter spare part siphon with horizontal outlet DN 50, order no. 89582.7 Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-TAMARO-VS, sanitary ceramic, electronic controlled with Bluetooth
EN 80, EN 13407, EN 15091, dimensions 400 x 365 x 770 mm
minimum 1 l - 3.0 l flush, water inlet concealed 1/2", outlet horizontal, flushing rate minimum 0.3 l/s
electronic control 230 V / 6 V
Special feature: Vacuum and performance tested
1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)
Further options / accessories: 1-liter spare part siphon, LIS CU3 concealed frame for urinal with integrated control
Order no. 84112.5

TECHNICAL DRAWINGS / S 1 : 20

