

URINALS

Siphonic urinal ANTERO 84115.0



TECHNICAL DATA

| | |
|---------------------|---|
| Order no. | 84115.0 Charge 000 (DN 40) / Charge 401 (DN 50) |
| Certified to | EN 80, EN 13407, EN 15091 |
| matching for | LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5 |
| Specification | 1-l flushing electronic controlled siphonic urinal HF Electronic control for battery (6x LR6 AA 1,5 V) pre-assembled Ceramic siphon cover Siphon replaceable from top without dismantling urinal 1-l flushing automatic adjusted independent of supply pressure Lid under urinal Waste piping cleaning without dismantling urinal Only in combination with fixing set, order no. 89282.6 Charge 000 – DN 40 Charge 401 – DN 50 |
| Water inlet | concealed, 1/2" |
| Outlet | horizontal (variable 60 mm) |
| Flushing | minimum 0.5 l - 3.0 l |
| Flushing rate | minimum 0.3 l/s |
| Weight | 25,0 kg |
| Mounting acc. incl. | Electronic control pre-assembled Ceramic siphon cover, order no. 89213.0 laufen EasyFit system M8, order no. 89282.6 |

| | |
|---------------------|--|
| Mounting acc. incl. | Charge 000 – 1-liter siphon with waste connection pipe DN 40 Charge 401 – 1-liter siphon with waste connection pipe DN 50 |
| Mounting acc. excl. | 1-liter spare part siphon, order no. 89313.6 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4 |
| Colours | see colour table |

SPECIFICATION TEXT

Siphonic urinal Laufen-ANTERO, sanitary ceramic electronic controlled
EN 80, EN 13407, EN 15091, dimensions 380 x 365 x 770 mm
min. 0.5 l - 3.0 l flushing automatic adjusted independent of supply pressure, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal (variable 60 mm), flushing rate minimum 0.3 l/s HF electronic control for battery (6x LR6 AA 1,5 V) pre-assembled, siphon replaceable from top without dismantling urinal, lid under urinal, waste piping cleaning without dismantling urinal
Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)
Further options / accessories: 1-liter spare part siphon, LIS CU3 concealed frame for urinal with integrated control
Order no. 84115.0

TECHNICAL DRAWINGS / S 1 : 20

