

**Siphonic urinal
ANTERO
84115.2**



TECHNICAL DATA

Order no.	84115.2 Charge 000 (DN 40) / Charge 401 (DN 50)
Certified to	EN 80, EN 13407, EN 15091
matching for	LIS CU3 Concealed frame for urinal with integrated control, order no. 89266.5
Specification	1-l flushing electronic controlled siphonic urinal HF Electronic control with Bluetooth for 230 V / 12 V pre-assembled Ceramic siphon cover Siphon replaceable from top without dismantling urinal 1-l flushing automatic adjusted independent of supply pressure Lid under urinal Waste piping cleaning without dismantling urinal Only in combination with fixing set, order no. 89282.6 Charge 000 – DN 40 Charge 401 – DN 50
Water inlet	concealed, 1/2"
Outlet	horizontal (variable 60 mm)
Flushing	minimum 0.5 l - 3.0 l
Flushing rate	minimum 0.3 l/s
Weight	25,0 kg
Mounting acc. incl.	Electronic control 230 V / 12 V pre-assembled Ceramic siphon cover, order no. 89213.0 laufen EasyFit system M8, order no. 89282.6

Mounting acc. incl.	Charge 000 – 1-liter siphon with waste connection pipe DN 40 Charge 401 – 1-liter siphon with waste connection pipe DN 50
Mounting acc. excl.	1-liter spare part siphon, order no. 89313.6 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4 USB Adapter module, order no. 89013.0 GLT Adapter module, order no. 89013.1 Bluetooth Adapter module, order no. 89113.2
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal Laufen-ANTERO, sanitary ceramic, electronic controlled with Bluetooth
EN 80, EN 13407, EN 15091, dimensions 380 x 365 x 770 mm
min. 0.5 l - 3.0 l flushing automatic adjusted independent of supply pressure, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal (variable 60 mm), flushing rate minimum 0.3 l/s, HF electronic control 230 V / 12 V pre-assembled, siphon replaceable from top without dismantling urinal, lid under urinal, waste piping cleaning without dismantling urinal
Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)
Further options / accessories: 1-liter spare part siphon, LIS CU3 concealed frame for urinal with integrated control
Order no. 84115.2

TECHNICAL DRAWINGS / S 1 : 20

