

**Siphonic urinal rimless
LEMA
84119.3**



TECHNICAL DATA

Order no.	84119.3 Charge 000 (DN 40) / Charge 401 (DN 50)
Certified to	EN 80, EN 13407
matching for	LIS CU2 Concealed frame for urinal without integrated control, order no. 89266.4 LIS SMART CONTROL-U, order no. 37066.0
Specification	Rimless 1-l flushing siphonic urinal Ceramic siphon cover Siphon replaceable from top without dismantling urinal Only in combination with fixing set, order no. 89280.8 Charge 000 – DN 40 Charge 401 – DN 50
Water inlet	concealed 1/2"
Outlet	horizontal (variable 60 mm)
Flushing	minimum 0.5 l - 3.0 l
Flushing rate	minimum 0.3 l/s
Weight	24,5 kg
Mounting acc. incl.	Ceramic siphon cover, order no. 89213.0 Wall fixing set M8 LAUFEN, order no. 89280.8 Charge 000 – 1-liter siphon with waste connection pipe DN 40 Charge 401 – 1-liter siphon with waste connection pipe DN 50

Mounting acc. excl.	LIS CU2 horizontal inlet connection, order no. 89009.7 1-liter spare part siphon, order no. 89313.6 Stone screw fixing set M8 Adaption set for stone screws M10, order no. 89281.6 Adaption set for stone screws M12, order no. 89281.4
Colours	see colour table

SPECIFICATION TEXT

Siphonic urinal rimless Laufen-LEMA, sanitary ceramic EN 80, EN 13407, dimensions 350 x 420 x 730 mm minimum 0.5 l - 3.0 l flush, ceramic siphon cover, water inlet concealed 1/2", outlet horizontal (variable 60 mm), flushing rate minimum 0.3 l/s siphon replaceable from top without dismantling urinal, Special feature: Vacuum and performance tested, 1-litre siphon, waste connection pipe DN 50 (standard Europe, except CH and UK) and pipe DN 40 (standard CH)
Further options / accessories: LIS horizontal inlet connection, 1-liter spare part siphon, LIS CU2 concealed frame for urinal without integrated control
Order no. 84119.3

TECHNICAL DRAWINGS / S 1 : 20

