

LAUFEN INSTALLATION SYSTEM

CH1

Support bar for handle and holding systems 89266.7



TECHNICAL DATA

Order no.	89266.7	Other specifications	Galvanized leg support, height-adjustable 0-200 mm.
Certified to	DIN 18024-2, (Support bar ISO 9227, Wood Panel EN 13986)		Support bar made of steel profile.
matching for	Concealed frame for wallhung WC CW1, order no. 89466.0, 89466.5 CW2, order no. 89466.1, 89466.6 CW3, order no. 89466.2 CWN1, order no. 89466.7 Concealed frame for wallhung bidet CB1, order no. 89266.0,		Capable to resist 100 kg of vertical force and 35 kg of horizontal force.
Specifications	For mounting in front of a solid or drywall construction and also assembled to left side of LIS CW1, CW2, CW3, CWN1, CB1 (WC / Bidet), self-supporting. The frame includes a wood panel made of pitch pine plywood BFU100, adjustable in height between 600-920 mm	Installation depth	135-205 mm
		Weight	5,0 kg
		Mounting acc. incl.	Extensible fastening bracket to the wall with fixing kit, fastening set to floor and wall, 2 screws and 2 washers for fixing the frame to the side of the LIS (only concealed frame for wallhung WC or wallhung bidet), 5 screws for installation between modular walls.
		Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of the bar recommended to 850 mm, adjustable to different heights. System installation is also possible between modular walls (plasterboard).
		Colours	Surface powder coated blue (support bar)

TECHNICAL DRAWINGS / S 1 : 20

