

# LAUFEN INSTALLATION SYSTEM

## CW3

### Concealed self-supporting frame with cistern for wallhung WC 89466.2



#### TECHNICAL DATA

Order no.	89466.2
Certified to	EN 14055
matching for	All LAUFEN wallhung toilets
Specifications	For self-supporting installation on a drywall construction, support wall is not needed, with frontal actuator, with water condensation insulation. Dual-Flush 6/3-l (4/2-l-flush). Flush valve with silicon seal. Fill valve with anti-siphon system.
Other specifications	Galvanized leg supports, height-adjustable 0-200 mm. Self-supporting frame made of steel profiles. Capable to resist 400 kg
Water inlet	top or rear R 1/2", brass
Outlet	DN 90/110
Flow pressure range	0.5-10 bar
Water temperature	max. 25°C
Tank	Thickness 110 mm, material PP
Installation depth	160 mm

Weight	22,0 kg
Mounting acc. incl.	Fastening set to floor, WC connection set, tiling set, protection caps (for WC connection pipes) and protection tubes for M12 threaded rods, angle valve 1/2".
Mounting acc. excl.	Fastening set for the wall, order no. 89563.5
Accessories excl.	Actuator plates dual flush, order no. 89566.1, 89566.2 (stainless steel) Electronic actuator plate dual flush, order no. 89566.3, 89566.4 Support bar for handle and holding systems, order no. 89266.7, 89266.8
Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of WC pre-set to 400 mm, adjustable between 390-450 mm. System installation is also possible between modular walls (plasterboard).
Colours	Surface powder coated blue

#### TECHNICAL DRAWINGS / S 1 : 20

