

# BARRIERS: CLASSIC



| Category: [BOLLARDS / BARRIERS](#)

## PRODUCT DESCRIPTION

Designer: [Studiorange](#)

The CLASSIC barrier is made of 2 posts, made - in the middle, lower and upper part - in tubular steel 80 mm diam. and 1,5 mm thickness, whereas the two sections of H. 40 mm are made in tubular stainless steel AISI 316 of 76 mm diam. and 2 mm thickness. The tubes of different diameters are fixed together with a mechanical system through specific screws M5.

In the stainless steel sections, brackets 50/10 thickness, supporting a tubular structure made in square tube 20x20x2 mm., are welded. Inside the frame, a steel panel 20/20 thickness, is fixed as a support for the advertisements. On the base of the barrier there are 2 flanges, with 4 holes 10 mm diam. for the fixing to the ground through specific bolts (not provided). The version for the fixing through cementation is provided with an under flange extension of 250 mm and the flange comes with no holes.

For the realization of this product made in Italy, Steel EN10111DD11 is used and later treated with a cycle of sandblasting, cataphoresis and powder coating. Such cycle is meant to guarantee the protection of the painted products, in an environment of C4 corrosion class, as requested by the UNI regulations EN ISO 12944-2. The products are eventually polyester-powder coated with RAL colours at choice.

Optional: *extension for cementation*

### Max dimensions:

Height: **1000 mm**  
Length: **1480 mm**

### Panel:

Height: **800 mm**  
Length: **1200 mm**

Weight: **34 kg**

Material: [steel](#)

