

COPENHAGUE - Fixed side

CHARACTERISTICS

- Tempered transparent glass Standard EN- 12150 6 mm door and fixed.
- 20 mm expansion per profile.
- Height 1950 mm (H).
- No interior profile



Ultra-Protect
OPTIONAL ANTI-SCALING TREATMENT



CERTIFIED
BY TUV
NORMA
EN-14428

DO NOT USE
ABRASIVE
PRODUCTS

MEASURES AVAILABLE FOR FIXED SIDE

Dimensions (F)	Dimensions and packaging weight according to measurement in mm.					
Dimensions (F)	Width mm.	Depth mm.	Hight mm.	Net weight Kg.	Gross weight Kg.	Nº of packaging
680 - 700	775	85	2050	22,4	23,3	1
780 - 800	875	85	2050	25,7	26,5	1
880 - 900	975	85	2050	29,2	30	1

Hight (H): 1950 mm.

MEASURES AVAILABLE FOR SPECIAL FIXED SIDE

Dimensions (F)	Dimensions and packaging weight according to measurement in mm.					
Dimensions (F)	Width mm.	Depth mm.	Hight mm.	Net weight Kg.	Gross weight Kg.	Nº of packaging
<600	700	105	2080	22,4	19,2	1
600 - 800	900	105	2080	28,4	25	1
800 - 1000	1100	105	2080	34,7	30,9	1
1000 - 1200	1300	105	2080	40,54	36,7	1

Hight (H): 1950 mm.

