

#### Features

- Low-threshold design for easy entry and exit.
- Covered drain with removable cover.
- Single threshold for alcove installation.
- Center drain.
- Coordinates with other products in the Archer collection.

#### Material

- Acrylic.

#### Recommended Products/Accessories

K-9132 Shower Drain  
K-702011-L Frameless Pivot Shower Door  
K-702408-G54 Frameless Pivot Shower Door  
K-702408-L Frameless Pivot Shower Door  
K-705701-L Frameless Pivot Shower Door  
K-705709-L Frameless Pivot Shower Door  
K-705713-L Frameless Pivot Shower Door  
K-705721-L Frameless Pivot Shower Door  
K-705727-L Frameless Pivot Shower Door  
K-705739-L Frameless Pivot Shower Door  
K-705806-L Semi-Frameless Pivot Shower Door  
K-705820-L Semi-Frameless Pivot Shower Door  
K-705821-L Semi-Frameless Pivot Shower Door  
K-23726 Drain treatment  
K-23732 Tub & shower cleaner



#### Codes/Standards










CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662


#### KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	58	Thunder™ Grey
	7	Black Black™



### Technical Information

All product dimensions are nominal.

Installation:	Three-wall alcove
Drain location:	Center
Weight:	44 lbs (20 kg)
Minimum floor load:	20 lbs/ft <sup>2</sup> (97.6 kg/m <sup>2</sup> )

### Notes

- Measure your actual product for rough-in details.
- Install this product according to the installation instructions.
- Shimming may be required to level the fixture.
- Shimming may be required between the stud frame and the fixture.
- Stud opening tolerance is + 1/4" (6 mm), - 0" (0 mm).