









Overview of technical details

	NEOREST AC	NEOREST EW	WASHLET™ SG	WASHLET™ RW	WASHLET™ RX EWATER+	WASHLET™ SX EWATER+	WASHLET™ GL 2.0*	WASHLET™ EK 2.0*	
									
WARM WATER SPRAY	Comfort spray flow rate	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0,27 to 0,43l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.29 to 0.60 l/min	0.29 to 0.60 l/min
	Soft flow rate	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0,27 to 0,43l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.29 to 0.55 l/min	0.29 to 0.55 l/min
	Lady shower flow rate	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0,29 to 0,43l/min	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.27 to 0.55 l/min	0.27 to 0.55 l/min
	Continuous-flow water heater	●	●	●	●	●	●		
	Warm water tank							0.75 l	0.75 l
	Warm water supply	unlimited	unlimited	unlimited	unlimited	unlimited	unlimited	40 seconds	40 seconds
	Adjustable water temperature	30 to 40 °C	30 to 40 °C	30 to 40 °C	30 to 40 °C	35 to 40 °C	35 to 40 °C	30 to 40 °C	35 to 40 °C
Water tank reheating time							approx. 15 min	approx. 15 min	
COMFORT	Heated seat, individually adjustable temperature	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C
	Deodoriser – Filter system performance	0.16m³/min	0.16m³/min	0.16m³/min	normal 0,09 m³/min, power 0,16 m³/min	normal 0,09 m³/min, power 0,16 m³/min	normal 0,09 m³/min, power 0,16 m³/min	0.16m³/min	0.16m³/min
	Dryer with adjustable temperature	35 to 55 °C approx. 0.29m³/min	35 to 55 °C approx. 0.29m³/min	35 to 55 °C approx. 0.29m³/min	37 to 55 °C approx. 0,29 m³/min			37 to 55 °C approx. 0.27m³/min	37 to 55 °C approx. 0.27m³/min
CONNECTIONS / PIPES	Power outlet required	●	●	●	●	●	●	●	●
	Water connection pressure	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10Bar	1 to 10bar	1 to 10bar	1 to 10 bar	1 to 10 bar
	Power input	1,289–1,527 W	1,289–1,527 W	1,290–1,528 W	1,455–1,468 W	1,437–1,451 W	1,444–1,459 W	276–321 W	276–321 W
	Connection limits	220–240 V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz	220–240V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz	220–240 V/50 Hz
ECO	EN 1717 (Drinking water safety)	●	●	●	●	●	●	●	●

* with side or hidden connections

WC-/WASHLET™ combinations

	NEOREST AC	NEOREST EW	WASHLET™ SG	WASHLET™ RW	WASHLET™ RX EWATER+	WASHLET™ SX EWATER+	WASHLET™ GL 2.0		WASHLET™ EK 2.0	
							with hidden connections	with side connections	with hidden connections	with side connections
WC	WC NEOREST AC with Zirconium coating	●								
	WC NEOREST EW		●							
	WC SG			●						
	WC RP				●	●				
	WC SP						●			
	WC MH						● CW162YH	●	● CW162YH	●
	WC NC							●		●
	WC ES							●		●