



TECHNICAL DATA

SIT CENTRAL LEG TABLE Ø120/Ø140 Designer: Andrés Bluth

Ø120x74 cm / Ø140x74 cm Ø47,2"x29,1"/Ø55,1"x29,1" FRAME

Material Finish Extruded aluminum

Polyester powder coating

TABLE TOP

Material

Iroko wood

Dekton porcelain 10mm

HPL Compact 10mm.: Solid phenolic core laminate. HPL and Dekton for its self has supporting capability, resistance to humidity, strength and dimensional stability. Resistant to cigarettes burns, staining,

chemicals and abrasion.

PAINTING COLORS

Powder coating colors

More than 15 availables p. coating colors in our Bivag current catalog.

ADITIONAL ITEMS

Waterproof cover

MANTEINANCE

Powder coating aluminum and Dekton

Powder coating aluminum Clean the surface regularly with warm water and neutral soap.

Iroko wood

Use a non-abrasive sponge or cloth.

Rinse with plenty of water immediately after cleaning. Iroko may change color or even crack due to humidity levels and sudden changes in temperature. Iroko undergoes a natural process of oxidation that affects its color, which

turns a silver-grey shade. Iroko furniture is treated with a waterproof $% \left(1\right) =\left(1\right) \left(1\right) \left($

sealant. We recommend treating the wood twice a year:

1. Dampen a rag with soap solution and gently wipe the surface of the wood. The soap solution will free the surface of dust and

contaminating agents from pollution. contaminating agents from pollution.

2. Once the soap solution has dried we will proceed to the application of the Cromaprotect water based re-toner. Dampen a sponge with the re-toner and apply onto the surface of the wood you want to treat.

Av. J.V. Foix 72-74 08034 Barcelona

Spain

Tel.: +34 93 205 75 95 info@bivaq.com www.bivaq.com

BOX WEIGHT - VOLUME

Ø120x74: 26 kg (iroko) / 41 kg (dekton) / 25 kg (compact) -0,15m3

Ø140x74: 33 kg (iroko) / 54 kg (dekton) / 33 kg (compact) -0,19m3

OTHERS

Suitable for outddor use. Resistant to weathering and sunlight.

COUNYTRY OF ORIGIN

Designed and manufactured in Barcelona, Spain