

ESAGONO collection

DECORATIVE OUTDOOR LIGHTING



DECORATIVE OUTDOOR LIGHTING

Maurizio Quargnale

portable lamp applique downlight bollard

ESAGONO collection

DECORATIVE OUTDOOR LIGHTING

Esagono is a product designed to ensure extreme flexibility. Because of its hexagonal section, this product can be placed at the base of walls or hedges, or used as a pole for garden or even it can be fixed to a wall. Esagono is also adjustable, obtaining effects of full or asymmetric lighting. Esagono has painted aluminium finishing and it is available in two different lengths.



ESAGONO collection

DECORATIVE OUTDOOR LIGHTING

spike version




Because of its hexagonal section, this product is extremely versatile and of great visual impact, obtaining effects of full lighting.













collection



 portable lamp IP65 IK 05
2 mm methacrylate frosted diffuser
600 mm
1200 mm







 downlight IP65 IK 05
2 mm methacrylate frosted diffuser
600 mm
1200 mm

 applique IP65 IK 05
2 mm methacrylate frosted diffuser
600 mm
1200 mm


 bollard IP65 IK 05
2 mm methacrylate frosted diffuser
600 mm
1200 mm


details



Extruded aluminium alloy body. A4 Stainless steel screws. Internal reflector with high luminous efficiency. Gore valve to prevent condensing inside the product. Support system in Scratch resistant rubber. The product, thanks to its hexagonal structure, can be rotated to 360° every 60°, directing the light to your own interest. The product is subjected to galvanic anodizing treatment divided into distinct phases: mechanical satin finishing, surface degreasing, anodic oxidation and finally fixing. Subsequently the product is painted by performing a double pass in-line process, which allows you to generate a single thick protective layer which then generates barrier against atmospheric agents and UV rays. This allows to achieve corrosion resistance performance in salt spray. Pre-treatment with atmospheric pressure plasma is carried out on the surface before gluing of the diffuser on Platek products.

standard finishes







lighting data

 600 mm
1200 mm
5 m cable length
orientable 360°

WHITE LED

| | | |
|---------------------------------------|--|--|
| | → 600 mm | → 1200 mm |
| 3000K CRI>80 220-240V 0/50/60Hz ⊕ |  11W 375 lm (*) orientable 360° sandblasted |  22W 750 lm (*) orientable 360° sandblasted |
| 2700K / 4000K available on request |  71° 508 cd/klm |  71° 508 cd/klm |

(*) Real Data