Certificate Number UL-US-L352710-11-62309102-1

Report Reference E352710-20190326

Date 2-Dec-2021

Issued to: Schneider Electric Industries S A, DBA Telemecanique

8001 Knightdale Blvd Knightdale, NC

United States 27545

This is to certify that NISD - Emergency Stop Devices representative samples of See Addendum Rage for Product

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision

Date: 2019-05-06, UL 60947-5-1, 3rd Ed., Issue Date: 2014-03-28, UL 60947-5-5, 1st Ed., Issue Date: 2017-08-

11, Revision Date: 2019-09-13

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





Certificate Number UL-US-L352710-11-62309102-1

Report Reference E352710-20190326

Date 2-Dec-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
XALK84W or XALK178W followed by one digit, followed	Illuminated Safety Actuator
by B or M, may be followed by three digits, followed by E	II. VIII. VIII. VIII. VIII. V
or G, followed by H7. (@)	LYALVALVALVALV
XB5AS84W followed by 3 or 4, followed by B, followed	Illuminated Safety Actuator, Emergency
by 5 or 41.	stop pushbutton with contact blocks,
	complete device
ZB5AS84W, followed by one digit, followed by B, G or M.	Illuminated Safety Actuator, Emergency
(@)	stop pushbutton operating heads
Safety Actuator label, ZBY8L, followed by three or four	Illuminated Safety Actuator,
digits.	PLATINGLATION
ZBY9W followed by one digit, followed by B, G or M,	Illuminated Safety Actuator, Illuminated ring
followed by three or four digits.	for emergency stop pushbuttons





Certificate Number UL-CA-L352710-31-62309102-1

Report Reference E352710-20190326

Date 2-Dec-2021

Issued to: Schneider Electric Industries S A, DBA Telemecanique

8001 Knightdale Blvd Knightdale, NC

United States 27545

This is to certify that NISD7 - Eme representative samples of

NISD7 - Emergency Stop Devices Certified for Canada

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: IEC 60947-5-5, Edition: 1.2, Issue Date: 2016-02-01

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.






Certificate Number UL-CA-L352710-31-62309102-1

Report Reference E352710-20190326

Date 2-Dec-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
XALK84W or XALK178W followed by one digit, followed	Illuminated Safety Actuator
by B or M, may be followed by three digits, followed by E	I. VII. VII. VII. VII. V
or G, followed by H7. (@)	LVALVALVALVALVA
XB5AS84W followed by 3 or 4, followed by B, followed	Illuminated Safety Actuator, Emergency
by 5 or 41.	stop pushbutton with contact blocks,
	complete device
ZB5AS84W, followed by one digit, followed by B, G or M.	Illuminated Safety Actuator, Emergency
(@)	stop pushbutton operating heads
Safety Actuator label, ZBY8L, followed by three or four	Illuminated Safety Actuator,
digits.	LVALVALVALVALV
ZBY9W followed by one digit, followed by B, G or M,	Illuminated Safety Actuator, Illuminated ring
followed by three or four digits.	for emergency stop pushbuttons





Bruce Mahrenholz, Director North American Certification Program