.25 PTLS01

.25 Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 2 1/8" Deck Thickness Minimum: 1/8" **Drain Assembly Materials: Brass** Drain Depth Maximum: 1 3/4" Drain Hole Diameter: 1 3/4" Drain Style: Push Touch

Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75, 2.2

Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 1/8"

Drain Depth Minimum: 1 1/4"

Height: 4"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male With Supply Nut

Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted

Length: 11 3/8" Number of Handles: Two Number of Holes: Three Hole Primary Material: Brass Spout Swivel: N

Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

.25 is the ultimate in utilitarian elegance: A simple and understated design that is equally functional and beautiful. Code # PTLS01: ASME A112.18.1 / CSA B125.1, ASME A112.18.2 / CSA

CODES & STANDARDS

B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA

PRODUCT FEATURES

Uses a simple pop-up drain that is closed and opened by pushing down on the stopper. Does not use a lift rod to operate the drain stopper.

The cross handle's anthropomorphic form is not only gentle in its execution, but also welcome to the touch. Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires 1.2gpm(4.5 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS





PRODUCT (NOTES)

Sold with European style drain; USA style drain sold separately for use with non-Waterworks sinks.

.25 PTLS01

.25 Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

