



TARSIUS collection

Piero Castiglioni





collection



floodlight

IP66
IK 10




4 mm methacrylate
transparent diffuser

0,5 m cable length



floodlight
pole-top

IP66
IK 10



4 mm methacrylate
transparent diffuser

pole available on request

8 m cable length

floodlight



WHITE LED

→ street optic

→ asymmetrical

3000K CRI>80
220-240V 50/60 Hz
DALI dimmable



54W | 5770 lm (*)
street optic



54W | 4020 lm (*)
asymmetrical

2200K / 2700K / 4000K
available on request



560 cd/klm



635 cd/klm

WHITE LED

→ street optic

→ asymmetrical

3000K CRI>80
220-240V 0/50/60 Hz
MIDNIGHT system included



49W | 4900 lm (*)
street optic



49W | 3685 lm (*)
asymmetrical

2200K / 2700K / 4000K
available on request





560 cd/klm



635 cd/klm

floodlight pole-top



WHITE LED

→ street optic

→ asymmetrical

3000K CRI>80
220-240V 50/60 Hz
DALI dimmable



54W | 5770 lm (*)
street optic



54W | 4020 lm (*)
asymmetrical

2200K / 2700K / 4000K
available on request



560 cd/klm



635 cd/klm

WHITE LED

→ street optic

→ asymmetrical

3000K CRI>80
220-240V 0/50/60 Hz
MIDNIGHT system included



49W | 4900 lm (*)
street optic



49W | 3685 lm (*)
asymmetrical

2200K / 2700K / 4000K
available on request



560 cd/klm



635 cd/klm

(*) Real Data

details

Die-cast body and flange made of aluminium alloy with very low copper content. High reflection anodized aluminium reflector. A4 Stainless steel screws. Gore valve to prevent condensing. The product is subjected to galvanic anodizing treatment divided into distinct phases: mechanical satin finishing, surface degreasing, anodic oxidation and finally fixing. Subsequently the product is painted by performing a double pass in-line process, which allows you to generate a single thick protective layer which then generates barrier against atmospheric agents and UV rays. This allows to achieve corrosion resistance performance in salt spray. PMMA diffuser Pre-treatment with atmospheric pressure plasma is carried out on the surface before gluing of the diffuser on Platek products.

standard finishes




.06 grey

on request finishes



.01 black



.02 white



.07 corten



.08 anthracite



.09 bronze