# MÉTRO - Single-lever thermostatic wall-mount shower mixer

## E24394





Collection: MÉTRO

#### Finish\*:





CP - Chrome BL

#### **Main features:**











#### **Features**

MATERIAL: BrassTYPE: Single-lever

HOLE CONFIGURATION: 150 ± 15
 SINGLE-LEVER TAP: THERMOSTATIC

• SAFETY STOP: 37°C
• WARM BODY: Yes

• FINISH GUARANTEE: 10 years

• INSTALLATION TYPE: 2 holes

. CONNECTION: With connectors and wall escutcheons

• WATER/ENERGY-SAVING: WATER-SAVING

INSTALLATION TYPE: 2 holes
 MAXIMUM TEMPERATURE: 50°C
 MECHANISM GUARANTEE: 5 years

### **Consumer benefits**

- MINIMALIST LINES: Delicate design blends harmoniously with all bathroom styles and matches all the ranges.
- ENHANCED NO-SCALD SAFETY: Maximum temperature 50°C and water automatically shuts off in case cold water is cut off.
- WARM BODY SAFETY: Hot water passageways are insulated at the rear of the mixer to avoid the risk of getting burned on the surface coming into contact with the skin.
- $\bullet$  PRACTICAL FOR DAILY USE: Ergonomic handle with built-in diverter for easy adjustment, even with wet or soapy hands.
- OPTIONAL SPACE SAVING SHELF: Add a textured, anti-slip shelf for daily items. Easy to mount and remove for cleaning. Order with E24315-NF or standard on E21767
- COMFORT : Thermostatic cartridge with extra-fast control ensuring constant water temperature, highly-accurate adjustment and selected temperature reached rapidly. Stop indicates comfort temperature (37°C).
- GUARANTEE OF HIGH QUALITY: Polished chrome finish guaranteed 10 years. Mechanisms guaranteed 5 years. Metal handles.


#### **Installation benefits**


HOT WATER HEATER COMPATIBILITY: Compatible with all water heaters of at least 18 kW.

#### **Optional products**

• E24315: Anti-slip shelf

#### **Technical drawing**





Product Specification: Single-lever thermostatic wall-mount shower mixer. E24394. Collection: MÉTRO. MATERIAL: Brass. INSTALLATION TYPE: 2 holes. TYPE: Single-lever. CONNECTION: With connectors and wall escutcheons. HOLE CONFIGURATION: 150 ± 15. WATER/ENERGY-SAVING: WATER-SAVING. SINGLE-LEVER TAP: THERMOSTATIC. INSTALLATION TYPE: 2 holes. SAFETY STOP: 37°C. MAXIMUM TEMPERATURE: 50°C. WARM BODY: Yes. MECHANISM GUARANTEE: 5 years. FINISH GUARANTEE: 10 years.