ALEO - Single-lever washbasin lever with 5135" system

E72277-4



Collection: ALEO

Finish*:







- MATERIAL: Metal
- NORMS AND REGULATION: NF : I ECAU : E00 Ch2 A3 U3 (Ps3) ACS : 10 ACCLY 113

Jacob Delafor PARIS

- FLOW RATE: 5 l/mn
- SPOUT PROJECTION: 98
- MECHANISM: Cartouche à disques céramique
- INSTALLATION TYPE: 1 hole

· WASTE : Without waste

• CONNECTION: With supply hoses

• INSTALLATION TYPE: 1 hole

• HEIGHT UNDER SPOUT: 142

• TYPE: Single-lever

Features • WEIGHT: 2 kg

• MECHANISM GUARANTEE: 5 years

Installation benefits

• DURABILITY: PEX high-resistance supply hoses

• INSTALLATION IN 35": Product equipped with the patented 5135" installation system for fast, easy mounting

• TOTAL SEAL: Centering washer replaces a flat washer to eliminate risk of slippage on the basin. No more adjusting needed for a well-sealed installation every time!


 STABILIZED MIXER: Washer centers and stabilizes the mixer and reduces risk of tipping in the basin during installation.

• NO-FALL HORSESHOE CLAMP: No more clamps falling into inaccessible nooks and crannies! With the fall-protection system, you can release the clamp with ease and continue the installation with your hands free.

• BUILT-IN PROTECTIVE WASHER: Protective washer remains in place and will not twist when tightened. Its innovative material protects the basin longer.

- QUICK NUT: Press and slide up rod in seconds.
- EXTRA-RESISTANT, ANTI-RUST NUT: Reinforced fibreglass nut. Resistance is twice the NF077 standard. Long-lasting material; will not rust. Can be removed easily even after several years.

Technical drawing



Product Specification: Single-lever washbasin lever with 5/35" system. E72277-4. Collection: ALEO. WEIGHT: 2 kg. MATERIAL: Metal. INSTALLATION TYPE: 1 hole. NORMS AND REGULATION: NF : I - ECAU : E00 Ch2 A3 U3 (Ps3) - ACS : 10 ACCLY 113. TYPE: Single-lever. FLOW RATE: 5 I/mn. HEIGHT UNDER SPOUT: 142. SPOUT PROJECTION: 98. CONNECTION: With supply hoses. MECHANISM: Cartouche à disques céramique. WASTE : Without waste. INSTALLATION TYPE: 1 hole. MECHANISM GUARANTEE: 5 years.