

Collection

REFLEX

Article

RX399

Description

Free standing bath filler spout

Box Dimensions


1105 x 400 x 150 mm

Weight


2.2 kg

Finishes

- **CC**
CHROME
- **CF**
BLACK CHROME
- **OO**
GOLD
- **BB**
ANTIQUE BRONZE
- **SS**
BRUSHED NICKEL
- **CS**
BRUSHED BLACK CHROME
- **BO**
MATT WHITE
- **NP**
MATT BLACK
- **IS**
BRUSHED PALE GOLD
- **OS**
BRUSHED GOLD
- **II**
PALE GOLD
- **RR**
ANTIQUE COPPER
- **RS**
ROSE GOLD
- **ON**
NATURAL BRASS
- **SR**
BRUSHED ROSE GOLD
- **PL**
PLATINUM



Dimensions



Cartridge

Treated fitting

Treated fitting G1/2" male

Aerator

M16.5x1

Flow Rate (+/-10%)

1 BAR
13.2 l/min

2 BAR
19.1 l/min

3 BAR
23.6 l/min

Production


Main body is a machined from a solid pieces

Material


BRASS
According to CuZn39PB3 (CW614N)
Max Lead content: 2.5%



IB RUBINETTI



Parts list			
ELEM	CODE	DESCRIPTION	QT
1	CPRX399C CXN_1	Preassembled free standing bath filler spout	1
1.1	AC0016746	Bridge spout Ø26 int. 240 L.439	1
1.2	AC0016747	Reduction for aerator M24x1M M16.5x1F	1
1.4	AQ0014729	Aerator cachè M16.5x1 neostrahl (01.5175.000)	1
1.5	AQ0001400	OR 20.35x1.78 NBR 70 SH	4
1.6	AS0016748	Fitting M24X1M	1
1.7	AC0016749	Pipe Ø26 th.1.5 L425	1
1.8	AQ0013888	Rosette Ø80 H15	1
1.9	AQ0006586	OR 25.12x1.78 NBR 70 SH	1
1.10	AS0016750	Flange Ø78.5 H.7	1
1.11	AS0016751	Connection Ø40 M24x1M	1
1.12	AQ0011059	OR 12x1.5 NBR 70 SH	2
2	AQ0015835	Inox screw M6x50 DIN933	4
3	AQ0013132	OR 70x2 NBR 70 SH	1
4	AS0016753	Fitting Ø340 G1-2M	1
5	AQ0010075	Inox rawplug M6 Ø10 L45	4



WARRANTY

All IB Rubinetterie SpA products are warranted for 10 years from the date of purchase, for the following cases:

- Defects of casting, porosity and chrome plating.
- Operating defects caused by incorrect fabrication.

The warranty provides for repair or replacement of products with fabrication defects recognized by our technical office. There is no other type of compensation anche the merchandise must be returned FOB our warehouse. The warranty only cover surface defects (scatches, dings, etc.) on fitting that have not been installed and used, returned in its original packaging with all components. O-ring, gasket seals and components subject to wear proportional to use are warranted for 2 years.

The warranty is void in the following cases:

Error installing and putting the product into service.

Deterioration of finisched surfaces due to use of cleaning products containing acids or abrasive substances. Deterioration of surface with finishes other than chrome plating. Their durability is, in fact, dependent on the user's care and gentleness of use.

Deterioration of the fitting due incorrect installation.

Improper repairs and maintenance performed without the company's prior authorization.

The warranty from IB Rubinetterie SpA is not renewable.

Cleaning

We recommended cleaning the finish surfaces with water and soap, using a soft cloth.

Do not use detergents that cointain hydrochloric acid or abrasive substances.

