

## METHVEN Satinjet<sup>®</sup>

## Satinjet° overhead II shower - NO ARM







CONSTRUCTION: Brass adjustable ball joint connection CLASSIFICATION: Suitable for all pressure systems WORKING PRESSURE: 35 - 500kPa DIMENSIONS FOR FITTING: 1/2" BSP OPERATING TEMPERATURE: 5 °C - 70 °C

- Features award-winning Satinjet<sup>®</sup> technology
  216mm diameter shower rose
- 21011111 utameter shower
- Easy to clean faceplate
- 3 star WELS rated on mains pressure (7.5 l/m)
- 2 star WELS rated on low pressure (11.0 l/m)

## OSRO230CPGR

## **Graphite faceplate**

http://www.methven.com/nz/showering/overhead-showers/kiri-satinjet-overhead-drencher





Satinjet<sup>®</sup>. The unmistakable feeling of 300,000 droplets per second.

Unlike conventional showers, Satinjet uses unique twin-jet technology to create optimum water droplet size and pressure, with over 300,000 droplets per second providing greater warmth and coverage. The result is an immersive, full-body experience.

FREEPHONE 0800 804 222 | FAX ORDERS 0800 805 222 | EMAIL CUSTOMERCARE@NZ.METHVEN.COM methven.com